



PRODUCT NAME :	PAR PRIMER SEALER 1035
DESCRIPTION :	<i>PAR Primer Sealer 1035 by Kansai is a premium grade, high performance water based sealer that is designed to protect the finish against chalking and efflorescence. Formulated with special styrene acrylic resins, PAR Primer Sealer 1035 will tolerate slightly damp surfaces.</i>
DESIGNED USE :	<i>Designed as a primer coat for use on new or previously painted interior and exterior masonry surfaces such as brickwork, plaster, cement rendering and asbestos cement.</i>
BINDER TYPE :	<i>Premium grade styrene acrylic binder pigmented with chalk resistant titanium dioxide and other high grade pigments.</i>
PERFORMANCE :	<ul style="list-style-type: none"> ▪ Good adhesion properties. ▪ Good build and excellent hiding power. ▪ Water based - odour. ▪ Helps prevent premature chalking or efflorescence. ▪ No added lead or mercury.
PHYSICAL PROPERTIES :	
Coverage*	10 – 12 m ² /Lt @ 35 microns
Volume Solids	38%
Dry Film Thickness	25 microns / coat
Wet Film Thickness	71 microns / coat
Flash Point	Not applicable
FINISHING :	
Colours	White.
Finish	Smooth matt finish.
Pack Size	5 & 20 litres.
APPLICATION :	
Drying Times	Surface dry : 15 min ; Recoat : 1-2 hours.
Dilution	Clean household water.
Cleaning Up	Clean household water.
DILUTION RATIO :	
Brush or Roller	Ready for use. if dilution is required, add up to 5% clean water.
Conventional Spray	Dilution of up to 10% water.
Airless Spray	Ready for use.
SPRAY EQUIPMENT GUIDE :	
Conventional Spray	A typical set up would be a minimum atomising pressure of 2.8 kg/cm ² and fluid pressure of 0.4 kg/cm ³ with a nozzle size of 0.43 mm.
Airless Spray	A typical set up would be a minimum of 155 kg/cm ³ with nozzle size of 0.38 - 0.43 mm and a spray tip angle of 65°.
	   
	<p>Application method 10-15 min drying time 65° spraying tip Practice proper cleaning</p>

SURFACE PREPARATION

New, unpainted surfaces : Exterior & Interior

Allow surfaces to cure and dry out at least 28 days. Large cracks must be repaired with cement sand mix and rendered smooth. Make good all minor defects with appropriate fillers. Remove all loosely adhering residues by thorough brushing.

Repainting : Interior

Check for powders or chalk. These surfaces contaminants must be completely removed by washing with warm water and detergent solutions. Rinse with clean water, taking care to change the rinsing water regularly. Primed surfaces with one coat Kansai Basecoat Sealer Water Based Wall Primer. If after thorough preparation the surface is still slightly powdery it may be necessary to seal it with PAR Plasterseal DPP 1001 Solvent Based Wall Sealer. (See product data sheet for details).



Seal a coat with primer



Use abrasive paper



Dust off

RECOMMENDED PAINT SYSTEM

New, unpainted surfaces & repainting : Exterior



New, unpainted surfaces & repainting : Interior



Limitations

- Not suitable for use on newly plastered walls that are not fully cured. PAR Primer Sealer DPP 1035 works best on surfaces with a moisture content of below 15% and alkalinity below pH-9 or otherwise premature paint failure may occur.
- Can tolerate slightly damp surfaces but not wet and water saturated surfaces.
- PAR Primer Sealer DPP 1035 is not a waterproofing coating. If waterproofing is required, seek specialist advice.

SAFETY & HEALTH INFORMATION

- Ensure adequate lighting and ventilation during application and drying.
- This product does not contain added lead or mercury.
- When applying paints, it is advisable to wear eye protection.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical assistance.
- Use soap and water to remove splashes from skin.
- Storage : Keep container closed and store in clean and dry conditions
- Do not empty into drains or water courses.
- This product is not flammable. Keep out of reach of children.
- Chemical Safety Data Sheet (CSDS) is available upon request.



Keep seal tight



Secure upright



Wear proper protection



Practice proper disposal

For further information on Product Data, please contact:

Decorative Sales Department
Kansai Paint Philippines, Inc.
Unit 8A South Luzon International Business Park, Brgy. Batino, Calamba City, Laguna 4027 Philippines.
Tel (Manila Line) : +63(2) 8519 4276 Tel (Laguna Line) : +63(49) 530 9876

* Practical coverage will vary according to the roughness and porosity of surface to be painted, the application method and condition, dry film thickness and the skill of applicator.

The information in this technical data sheet is given to the best of our knowledge based on laboratory testing and practical experience and is provided as a general advice only. No guarantee of results is implied since the conditions of use are beyond our control. It is the responsibility of the users to ensure the suitability and proper usage of the product. We reserve the right to change the data without prior notice.