

PRODUCT NAME :	PAR TIMBERCOTE
DESCRIPTION :	<i>PAR Timbercote by Kansai is a premium grade, translucent pigmented varnish which brings out the natural beauty of the grain of timber. It contains special preservatives to protect exterior timber surfaces against rot and mould growth.</i>
DESIGNED USE :	<i>As a decorative woodstain on exterior and interior timber surfaces where the natural beauty of wood grain is allowed to show through. Ideal for decorative doors, windows, handrails and pergola. It also acts as a protection that filter UV rays thereby reducing the traditional problems of cracking, flaking and peeling.</i>
BINDER TYPE :	<i>Premium grade synthetic resins with high grade lightfast pigments.</i>
PERFORMANCE :	<ul style="list-style-type: none"> ▪ Excellent resistance against wood rot and mould growth. ▪ Allow timber to breathe, thus will not blister or crack. ▪ Will filter out UV rays reducing degradation of timber. ▪ Excellent abrasion resistance. ▪ Long lasting protection and water resistant.
PHYSICAL PROPERTIES :	
Coverage*	12 – 14 m ² /Lt @ 25 microns
Volume Solids	33%
Dry Film Thickness	25 microns / coat
Wet Film Thickness	75 microns / coat
Flash Point	26°C
FINISHING :	
Colours	See PAR by Kansai Colour Book.
Finish	Translucent satin finish.
Pack Size	1 & 5 litres.
APPLICATION :	
Drying Times	Surface dry : 1 - 2 hours ; Recoat : 6-8 hours (Overnight for best results).
Dilution	Mineral turpentine.
Cleaning Up	Mineral turpentine.
DILUTION RATIO :	
Brush or Roller	Ready for use. if dilution is required, add up to 5% mineral turpentine.
Conventional Spray	Dilution of up to 10% mineral turpentine.
Airless Spray	Ready for use.
SPRAY EQUIPMENT GUIDE :	
Conventional Spray	A typical set up would be a minimum atomising pressure of 2.8 kg/cm ² and fluid pressure of 0.4 kg/cm ³ with a nozzle size of 1.27 mm.
Airless Spray	A typical set up would be a minimum of 155 kg/cm ³ with nozzle size of 0.38 - 0.43 mm and a spray tip angle of 65°.
	<div style="display: flex; justify-content: space-around; align-items: flex-end;"> <div style="text-align: center;">  <p>Application method</p> </div> <div style="text-align: center;">  <p>10-15 min drying time</p> </div> <div style="text-align: center;">  <p>65° spraying tip</p> </div> <div style="text-align: center;">  <p>Practice proper cleaning</p> </div> </div>

SURFACE PREPARATION

Properly Prepared New Wood
Surfaces must be clean, dry and free from all defective or poorly adhering materials.

Repainting : Wood
Previously painted surfaces must be thoroughly rubbed down using appropriate abrasive paper and dust off. Patch all holes and crevices with appropriate wood fillers. Ensure surfaces are clean, dry and free from all defective or poorly adhering materials.



Seal a coat with primer



Use abrasive paper



Dust off

RECOMMENDED PAINT SYSTEM

New, unpainted surfaces : Timber



Previously painted surfaces : Timber



Limitations

- Not recommended for masonry surfaces.
- Not recommended for timber floors. Use PAR Wood Finish for internal timber floors.

SAFETY & HEALTH INFORMATION

- This product contains white spirit. Ensure adequate lighting and ventilation during application and drying. Do not use in confined spaces. Keep windows and doors open at all times.
- This product does not contain added lead or mercury.
- When applying paints, it is advisable to wear eye protection.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Use soap and water to remove splashes from skin.
- Storage : Keep container closed and store in clean and dry conditions.
- Do not empty into drains or water courses.
- This product is flammable. Keep away from sources of ignition.
- Chemical Safety Data Sheet (CSDS) is available upon request.



Keep seal tight



Secure upright



Wear proper protection



Practice proper disposal

For further information on Product Data, please contact:

Decorative Sales Department
Kansai Paint Philippines, Inc.
Unit 8A South Luzon International Business Park, Brgy. Batino, Calamba City, Laguna 4027 Philippines.
Tel (Manila Line) : +63(2) 8519 4276 Tel (Laguna Line) : +63(49) 530 9876

* Practical coverage will vary according to the roughness and porosity of surface to be painted, the application method and condition, dry film thickness and the skill of applicator.

The information in this technical data sheet is given to the best of our knowledge based on laboratory testing and practical experience and is provided as a general advice only. No guarantee of results is implied since the conditions of use are beyond our control. It is the responsibility of the users to ensure the suitability and proper usage of the product. We reserve the right to change the data without prior notice.